



SHACMAN F3000 6x4 RIGID CHASSIS CAB MY24

HEAVYEQUIPMENT Diesel 2024

Car Code: SCF3004



ENGINE & TRANSMISSION

| | |
|-------------------|---|
| Model | WP12.380E22,6-in-line, water cooled, turbocharger |
| Power(kw/HP) | 280/380 (engine displacement 9.726) |
| Max. Torque/RPM | 1600/1200-1600 |
| Rated RPM | 2200 RPM |
| Emission standard | Euro II |
| Model | FAST GEAR 10JSD180 |
| Gears | 10 forwards & 2 reserve shifts |
| Clutch Type | 430 diaphragm-spring type |

DIMENSION, CAPACITIES & SUSPENSIONS

| | |
|------------------------|--|
| Complete kerb mass(kg) | 9500 |
| GVW(Tons) | 740T |
| Overall dimensions(mm) | 10000x2500x3300 |
| Wheelbase(mm) | 4575+1400 |
| Front axle | HANDE MAN 7500kg |
| Rear axle | HANDE MAN16000kg*2, double reduction axle with inter-wheel differential and different lock, Rear axle ratio:4.769" |
| Brake system type | Drum |
| Service brake | With dual-circuit compressed air brake |
| Parking brake | Power spring brake acting on rear wheel |
| Steering Type | ZF8098 technology, integral circulating ball power steering |
| Chassis Frame | 850x300(8+5) |
| Front suspension | Multi-plate leaf spring |
| Rear Suspension | Multi-plate leaf springs |
| Tires Type | 12.00R24*11 |
| Fuel Tank Capacity | 400L Aluminum Alloy Tank |
| Towing Device | Jost Ball pin type towing device |
| Cabin Devices | Auto A/C , Hydraulic driver seat , F3000 standard roof with single sleeping bunk, Manual cab tilting |
| Protection Type | Metal bumper , Front and Rear lamp protection |