



SHACMAN F3000 6x4 CHASSIS CAB MY25 Rigid Chassis Cab

CHASSISCAB Diesel 2025

Car Code: SCF3005



ENGINE & TRANSMISSION

Model	WP12.430E201,6-in-line, water cooled, turbocharger
Power(kw/HP)	316/430 (engine displacement 11.596L)
Max. Torque/RPM	2000/1000-1400
Rated RPM	1900 RPM
Emission standard	Euro II
Model	FAST 12JSD200T-B PTO
Gears	12 forwards & 2 reserve shifts
Max Input Torque (N.m)	2000

DIMENSION, CAPACITIES & SUSPENSIONS

Complete kerb mass(kg)	9400
GVW(Tons)	41 Tons
Overall dimensions(mm)	L 10500 X W 2550 X H 3300
Wheelbase(mm)	4575+1400
Clutch Type	430 diaphragm-spring type
Front axle	HANDE MAN 9500kg
Rear axle	HANDE MAN 16000kg*2, hub reduction axle with inter-wheel differential and different lock
Rear axle ratio	5.262
Brake system type	Drum brake
Service brake	With dual-circuit compressed air brake
Parking brake	Power spring brake acting on rear wheel
Steering Type	ZF8098 technology, integral circulating ball power steering
Chassis Frame	850x300(8+5), double plate chassis frame
Front suspension	Multi-plate leaf spring
Rear Suspension	Multi-plate leaf springs
Tires Type	12.00R24*11
Fuel Tank Capacity	400L Aluminum Alloy Tank
Cabin Type	SHACMAN F300 flat roof sleeper cab
Cabin Devices	Hydraulic driver seat, Auto A/C, Hydraulic cab suspension, Reverse buzzer, Manual cabtinting, Manual rear view mirror
Safety Device Type	ABS

INTERIOR FEATURES & SAFETY

Metal bumper	Oil pan protection
Fuel anti-theft system	Battery anti-theft system
Extra fuel filter	Front and rear light protection