



SHACMAN F3000 6x4 Tractor Head MY25

TRACTORHEAD Diesel 2025

Car Code: SHF3005



MOTEUR ET TRANSMISSION

Model	WP12.430E201,6-in-line, water cooled, turbocharger
Power(kw/HP)	316/430 (engine displacement 11.596)
Max. Torque/RPM	2000/1000-1400
Rated RPM	1900 RPM
Emission standard	Euro II
Model	FAST 12JSD200T-B+PTO
Gears	12 forwards & 2 reserve shifts
Max Input Torque (N.m)	2000

DIMENSIONS, CAPACITÉS ET SUSPENSIONS

Complete kerb mass(kg)	9500
GCW(Tons)	110 Tons
Overall dimensions(mm)	L 7000 x W 2550 x H 3500
Wheelbase(mm)	3175+1400
Clutch Type	430 diaphragm-spring type
Front axle	HANDE MAN 9500kg
Rear axle	HANDE MAN16000kg*2, hub reduction axle with inter-wheel differential and different lock
Rear axle ratio	4.769
Brake system type	Drum brake
Service brake	With dual-circuit compressed air brake
Parking brake	Power spring brake acting on rear wheel
Steering Type	ZF8098 technology, integral circulating ball power steering
Chassis Frame	850x300(8+7), double plate chassis frame
Front suspension	Multi-plate leaf spring
Rear Suspension	Multi-plate leaf springs
Tires Type	12.00R24*11
Fuel Tank Capacity	400L Aluminum Alloy Tank
Fifth wheel	90 #
Cabin Type	SHACMAN F300 flat roof sleeper cab

CARACTÉRISTIQUES INTÉRIEURES ET SÉCURITÉ

Air driver seat	Auto A/C
Hydraulic cab suspension,	Reverse buzzer
Manual cab titling	Manual rear view mirror

ABS

CARACTÉRISTIQUES EXTÉRIEURES

Steel bumper	Oil pan protection grid
Fuel anti-theft system	Battery anti-theft system
Extra fuel filter	Front and rear light protection